



Ultra Vac Model: UV-1

Standard Features

- 40GPH Process Flow Rate
- 1.5kW 110V Heater w/ Thermostat
- Gast Diaphragm Vacuum Pump
- Electrical Controls, w/ "On" indicator, "On/Off" switch
- 110V-1Ph-60Hz Power
- Adjustable Flow Control
- W22"xL22"xH45"
- 285 lbs.
- Spin on Filter w/ 5 micron element
- 4" Caster Wheels
- 25' Electrical Cord
- 10' Inlet & Outlet Hoses
- Pick-Up Wand
- One Year Warranty
- Operational & Maintenance Manual w/ Spare Parts List

Safety Features

- High Temp Shutdown Circuit
- High Oil Level Shutdown
- Feed Shutoff Valve

Standard Options

- Fork Lift Pockets
- Heat Recovery System
- Pressure Based Flow Sensor

The UV-1 is a highly efficient, compact vacuum dehydration unit capable of removing water from most lubricating, EHC and hydraulic fluids. Weighing only 285 pounds, the UV-1 is ideal for applications requiring mobility between machines or facilities. It is designed for 25 -125 gallon systems. The UV-1 requires a 110 volt, 20 AMP power supply. Options and custom modifications are available.



INDUSTRIAL FLUID SYSTEMS

22200 Ryan Road
Warren, MI 48091

Phone: 800-343-8106

Fax: 586-754-8284

www.industrialfluidsystems.com